



Husqvarna K 970 Rescue

Our largest rescue cutter is the Husqvarna K 970 Rescue. It has the best power/weight ratio of any other rescue cutter on the market.



ERGONOMIC AND EASY CUTTING

Efficient cutting with less strain on your body, thanks to its low weight, ergonomic handle and low vibrations.



FITS MULTIPLE BLADE BUSHINGS

Blades with 20mm and 25.4mm bore can be fitted thanks to the reversible blade bushing.



HIGH POWER WITH LESS FUEL

Our built-in automatic filter compensation SmartCarb™ maintains high power and lowers fuel consumption.



LIGHT AND POWERFUL

A light, compact and powerful machine with superior power-to-weight ratio.

Features Husqvarna K 970 Rescue

- Long service intervals
- Low fuel consumption and emissions
- The only time the filter needs to be checked and changed is if you experience lack of power.
- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- The drive belt with fully sealed transmission keeps out cutting dust for reduced wear and allows close cutting to walls and floor.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Specially designed starter handle, with room for heavy gloves.
- Adjustable carry strap allows full freedom of movement.
- For high visibility in smoke and water spray, which enhances control of the cutter.
- Our X-Torq® engine produces less emissions, has lower fuel consumption and results in more power.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- The cutting arm is reversible which lets you cut closer to walls or the ground. The drive belt has a fully sealed transmission. This keeps out cutting dust etc, reducing wear.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.

TECHNICAL SPECIFICATION

| | |
|---------------------------------------|----------------------------|
| Engine | Air-cooled 2 stroke engine |
| Cylinder displacement | 5.71 cu.inch |
| Power output | 6.5 hp |
| Fuel tank volume | 33.8 fl oz |
| Idling speed | 2700 rpm |
| Vibrations front handle | 3.7 m/s ² |
| Vibrations rear handle | 4.5 m/s ² |
| Sound pressure level at operators ear | 104 dB(A) |
| Sound power level, guaranteed (LWA) | 114 dB(A) |
| Blade diameter | 14 inch |
| Max cutting depth | 5 inch |
| Arbor Size | 1 inch |
| Weight (excl. cutting equipment) | 24.2 lbs |
| Fuel tank volume | 2.1 US pint |

