

GENERATING SET GE 3200 L FAMILY



- Lombardini, Gasoline engine
- Oil alarm shut off
- Single-phase synchronous alternator
- Overload protection
- Battery charger 12V - 10A
- Protective frame
- Silenced (S)
- Portable
- Meets EEC directives

Standard equipment 										
	Gasoline engine	Air cooling	Manual recoil	Oil alert	Engine shut down (oil)					
	Synchronous alternator	Ground fault interrupter	Thermal shut off	Socket 230V Schuko	Battery charger	Fuse				

Options on request

- Plug 230V 16A 2PT (M) SCHUKO
- Earthing Kit MT 10

Technical Data

GE 3200 L FAMILY

A.C. GENERATION	50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless
Single-phase generation	3 kVA (2.4 kW) / 230 V / 13 A
Battery charger d.c.	12V - 10A
Duty cycle	100%
Power factor (Cos φ)	0.8
Insulation class	H
On request other voltages and frequencies (60 Hz)	

ENGINE	Gasoline, 4-stroke, air cooled
Type	Lombardini LGA 226
Output*	3.5 kW (4.8 HP)
Speed	3000 rpm
Displacement	220 cm ³
Cylinders	1
Fuel consumption	410 g/kWh
* Maximum output according to ISO 3046/1	

GENERAL SPECIFICATIONS	
Tank capacity	3.1 l
Runnig time (Load 75%)	2.5 h
Protection	IP 23
Dimensions Lxwxh (mm)	675x375x430
Weight	39 kg
Noise level	98 LWA (71 dB(A) - 7 m)